
K-LKM 7,8 UWB

Non-interchangeable quick disconnect couplings DN 7.8

Özellikler



Çalışma basıncı	0 - 35 bar, maximum static working pressure (non-pulsating)
Akış hava	1.800 l/min (at 6 bar and Δp = 0.5 bar)
Akışkan sıcaklığı	-20 °C to +100 °C
Gövde	Brass
Valf	Die-cast zinc, nickel-plated
Kilidi açma kovanı	Anodised aluminium
Yay, patlama halkası, bilyeler	stain less steel
Yalıtım malzemesi	NBR

Açıklama

Standard push-in plugs for couplings DN 5 and DN 7.2 – DN 7.8 are compatible with these non-interchangeable couplings.
Diğer bilgiler, istek üzerinedir.

Açıklama

One-hand quick disconnect couplings with a large bore. Different media can be connected safely and non-interchangeably even when space is restricted, thanks to the colour-coded coupling and plug and the different coupling profiles defined for each of the four colours. Only couplings and plugs of the same colour fit together.

Ürün

Tanım	Bağlantı	Renk	Uzunluk (mm)	SW (mm)
K- 07 35 08 01	G 1/4 male	yeşil	57,5	19
K- 07 35 08 02	G 3/8 male	yeşil	57,5	19
K- 07 35 08 03	G 1/4 female	yeşil	55,5	19
K- 07 35 08 04	G 3/8 female	yeşil	54,5	19
K- 07 35 08 05	G 1/4 male	Brown	57,5	19
K- 07 35 08 06	G 3/8 male	Brown	57,5	19
K- 07 35 08 07	G 1/4 female	Brown	55,5	19
K- 07 35 08 08	G 3/8 female	Brown	54,5	19
K- 07 35 08 09	G 1/4 male	mavi	57,5	19
K- 07 35 08 10	G 3/8 male	mavi	57,5	19
K- 07 35 08 11	G 1/4 female	mavi	55,5	19
K- 07 35 08 12	G 3/8 female	mavi	54,5	19
K- 07 35 08 13	G 1/4 male	kırmızı	57,5	19
K- 07 35 08 14	G 3/8 male	kırmızı	57,5	19
K- 07 35 08 15	G 1/4 female	kırmızı	55,5	19
K- 07 35 08 16	G 3/8 female	kırmızı	54,5	19

Titiz kontrole rağmen hatalar önlenemez ve sorumluluk altında bırakmayan bilgiler hakkında hiçbir sorumluluk kabul edilmez.