
## K-INLINE-EJEKTTOREN VR

Inline ejectors »VR«, screw connection



| Özellikler   |  |
|--------------|--|
| Özellikler   | Vacuum generator with high maximum vacuum level (85% vacuum) No moving parts, which means no wear and no maintenance ultra small footprint, suitable for confined spaces minimal air consumption \nlow noise |
| Uygulama     | by screwing / plugging into the distribution beam direct attachment to the suction pad for handling various workpieces   |
| Gövde        | Aluminium eloxed (type VR)   |
| Meme sistemi | Brass (type VR)  |
| Bağlantı     | Fiş bağlantısı   |





## **Açıklama**

Diğer bilgiler, istek üzerinedir.

## **Açıklama**

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

| Ürün           |                   |                         |                             |                     |                     |                                  |                                     |                      |                             |  |  |
|----------------|-------------------|-------------------------|-----------------------------|---------------------|---------------------|----------------------------------|-------------------------------------|----------------------|-----------------------------|--|--|
| Tanım          | Meme<br>büyüklüğü | Atık hava<br>bağlantısı | Basınçlı hava<br>bağlantısı | Vakum<br>bağlantısı | Tahliye<br>derecesi | Hava tüketimi<br>emme<br>(L/min) | maks. emme<br>kapasitesi<br>(L/min) | Uzunl-<br>uk<br>(mm) | Çalışma<br>basıncı<br>(bar) |  |  |
| K- 07 45 01 29 | 0,7               | M 5 male                | G 1/4 IG                    | G1/8 female         | 90 %                | 21,0                             | 14,0                                | 35,0                 | 5,0                         |  |  |
| K- 07 45 01 30 | 0.9               | M 5 male                | G 1/4 IG                    | G1/8 female         | 89 %                | 36.0                             | 21.0                                | 35,0                 | 5.0                         |  |  |

14.12.2025 HANSA-FLEX AG www.hansa-flex.com