

K-INLINE-EJEKTTOREN SLP

Inline ejectors »SLP«, plug connection

Özellikler

Özellikler	Vacuum generator with high maximum vacuum level (85% vacuum) No moving parts, which means no wear and no maintenance ultra small footprint, suitable for confined spaces minimal air consumption \nlow noise
Uygulama	by screwing / plugging into the distribution beam direct attachment to the suction pad for handling various workpieces
Gövde	plastic (Typ SLP)
Meme sistemi	Brass (type VR)
Bağlantı	thread connector





Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

For vacuum generation directly at the point of use. For direct installation between the suction pad and the compressed air supply. Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector and flows through a nozzle. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet. This air and the driving air leave the ejector and enter the atmosphere via the exhaust air outlet.

Ürün

Tanım	Meme büyüklüğü	Atık hava bağlantısı	Basınçlı hava bağlantısı	Vakum bağlantısı	Tahliye derecesi	Hava tüketimi emme (L/min)	maks. emme kapasitesi (L/min)	Uzunluk (mm)	Çalışma basıncı (bar)
K- 07 45 01 27	0,5	-	4 mm	4 mm	85 %	13,0	8,0	57,0	4,5
K- 07 45 01 28	0,7	-	4 mm	4 mm	85 %	25,0	16,0	57,0	4,5

Titiz kontrole rağmen hatalar önlenemez ve sorumluluk altında bırakmayan bilgiler hakkında hiçbir sorumluluk kabul edilmez.