

K-KOMPAKTEJEKTOREN CP

Compact ejectors »CP«, digital vacuum switch with air-saving function

HANSA**FLEX**


Özellikler

Özellikler	Vacuum generator with integrated control valves and system monitoring functions Gripping and blowing off can be controlled without the need for external valves Optimised air consumption thanks to many models with differing suction capacities Minimum energy costs in continuous operation thanks to automatic air-saving Easy adjustment with foil keypad and LED display of the settings
------------	--

Uygulama	Handling of air-tight or slightly porous workpieces in fully automated handling systems e.g. in the robotics, automotive, packaging, electronics, electrical engineering and metalworking industries
----------	--

Temel cisim	Anodised aluminium
-------------	--------------------

Entegre olarak	NC blow-off valve, filter, silencer, non-return valve
----------------	---



Açıklama

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy. Diğer bilgiler, istek üzerinedir.

Açıklama

Purely pneumatic vacuum ejector that operates on the Venturi principle. Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C.

Ek bilgiler

Important: Order two connection plugs per ejector. A cable set is included with the compact ejector with automatic air-saving.

Ürün

Tanım	Meme büyüğü	Emme valfi bekleme konumu	Basınçlı hava bağlantısı	Vakum bağlantısı	Hava tüketimi emme (L/min)	maks. emme kapasitesi (L/min)	Tip	Çalışma basıncı (bar)
K-07 45 01 33	1,5	NC	G 1/8 IG	G1/8 female	117,0	65,0	72mm x 20mm x 164mm	5,0
K-07 45 01 34	1,5	NO	G 1/8 IG	G1/8 female	117,0	65,0	72mm x 20mm x 164mm	5,0
K-07 45 01 37	2,0	NC	G 1/4 IG	G 3/8 female	190,0	116,0	113mm x 22mm x 168mm	6,0
K-07 45 01 38	2,0	NO	G 1/4 IG	G 3/8 female	190,0	116,0	113mm x 22mm x 168mm	6,0
K-07 45 01 41	2,5	NC	G 1/4 IG	G 3/8 female	310,0	161,0	113mm x 22mm x 183mm	6,0
K-07 45 01 42	2,5	NO	G 1/4 IG	G 3/8 female	310,0	161,0	113mm x 22mm x 183mm	6,0

Aksesuar

K-ANSCH KABEL VAKUUMSCHAL	Connection cable for vacuum switch
---------------------------	------------------------------------

K-ERSATZSCHALLDAEMPFER 2	Replacement silencers
--------------------------	-----------------------

K-ERSATZFILTERELEMENTE	Replacement filter element
------------------------	----------------------------