K-BALGSAUGER 1,5 NBR

Bellows suction pads, round, 1.5 folds, material NBR



Özellikler

Özellikler

high rigidity of the upper fold Soft, tapered sealing lips Support surfaces on the bottom

high suction power optimum damping effect

very good adaptation to curved or uneven material

Kullanım Alanı Handling of highly uneven parts (e.g.tubes)

\nHandling of highly sensitive parts



Açıklama

Mini-sensor with housing and connection cable, analogue or digital output signal. Minimum size and low weight combined with high measuring accuracy. Diğer bilgiler, istek üzerinedir.

Açıklama

Robust and hard-wearing suction pad with a single sealing lip. Used wherever objects (parts, packing materials, etc.) need to be lifted, transported, turned over or handled in some other manner. It is also ideal when it is necessary to compensate varying workpiece heights or uneven surfaces or to handle easily damaged parts. It acts as the connecting element between the vacuum generator and the workpiece.

Ek bilgiler

Attention: The price does not include connection nipples. Please order separately.

Ürün					
Tanım	Bağlantı nipeli dişli dışı	Bağlantı nipeli dişli içi	Nipel dişli dış ile yapı yüksekliği	Nipel dişli iç ile yapı yüksekliği	Ø (mm)
K- 07 45 00 29	K-07450002 / K-07450004	K-07450007	21 / 22	28	11,0
K- 07 45 00 31	K-07450002 / K-07450004	K-07450007	21 / 22	28	14,0
K- 07 45 00 33	K-07450002 / K-07450004	K-07450007	24 / 25	31	16,0
K- 07 45 00 35	K-07450002 / K-07450004	K-07450007	20,5 / 21,5	27,5	20,0
K- 07 45 00 37	K-07450004	K-07450007	29	35	25,0
K- 07 45 00 39	K-07450003	K-07450006	31	42	33,0
K- 07 45 00 41	K-07450003	K-07450006	32	43	43,0
K- 07 45 00 43	K-07450003	K-07450006	38	49	53,0

Aksesuar

K-ANSCHLUSSNIP BALGSAUGER Connection nipples for bellows suction pads, round, 1.5 and 2.5 folds

26.11.2025 HANSA-FLEX AG www.hansa-flex.com