

K-FEDERSTOESSEL

Spring plungers

HANSA FLEX

Özellikler

Uygulama	Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured
Sıcaklık min.	0 °C
Sıcaklık max.	80 °C
Emici bağlantısı	M 3 female
Model	Spring plunger with high-strength steel rod, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide
Yay yolu	5,0 mm



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

Suitable for all round or oval suction pads in our standard range.

Ürün

Tanım	Vakum bağlantısı	Uzunluk (mm)	Dikey yük (N/m ²)
K- 07 45 00 73	M 3 female	33,5	550
K- 07 45 00 76	M 5 female	41,2	1500
K- 07 45 00 74	M 5 female	47,2	1500
K- 07 45 00 75	M 5 female	59,2	1500
K- 07 45 00 70	G 1/8 female	80,0	3700
K- 07 45 00 67	G 1/8 female	95,0	3700
K- 07 45 00 71	G 1/8 female	93,0	3700
K- 07 45 00 68	G 1/8 female	124,5	2400
K- 07 45 00 72	G 1/8 female	124,0	2400
K- 07 45 00 69	G 1/8 female	154,0	2400