

K-FEDERSTOESSEL

Spring plungers

HANSA FLEX

Özellikler

| | |
|-------------------------|--|
| Uygulama | Handling of workpieces with differing heights (eg. Curved metal sheets) Handling of very sensitive workpieces, very soft landing is assured |
| Sıcaklık min. | 0 °C |
| Sıcaklık max. | 80 °C |
| Emici bağlantısı | M 3 female |
| Model | Spring plunger with high-strength steel rod, guide sleeve and lower damping spring Plunger rod with integrated vacuum guide |
| Yay yolu | 5,0 mm |



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

Suitable for all round or oval suction pads in our standard range.

Ürün

| Tanım | Vakum bağlantısı | Uzunluk (mm) | Dikey yük (N/m ²) |
|----------------|------------------|--------------|-------------------------------|
| K- 07 45 00 73 | M 3 female | 33,5 | 550 |
| K- 07 45 00 76 | M 5 female | 41,2 | 1500 |
| K- 07 45 00 74 | M 5 female | 47,2 | 1500 |
| K- 07 45 00 75 | M 5 female | 59,2 | 1500 |
| K- 07 45 00 70 | G 1/8 female | 80,0 | 3700 |
| K- 07 45 00 67 | G 1/8 female | 95,0 | 3700 |
| K- 07 45 00 71 | G 1/8 female | 93,0 | 3700 |
| K- 07 45 00 68 | G 1/8 female | 124,5 | 2400 |
| K- 07 45 00 72 | G 1/8 female | 124,0 | 2400 |
| K- 07 45 00 69 | G 1/8 female | 154,0 | 2400 |