

K-SAUGPLATTENAUFHAENGUNG

Flexible suction pad mountings

Özellikler

Uygulama	For handling of workpieces with sloping using large-area vacuum gripper Handling of large plates that can sag when lifting In combination with spring plungers to compensate height-differences and Uneveness
Özel Nitelikler	very good adaptation to oblique workpiece surfaces automatic Rückstellung in die Ausgangslage vacuum-tight design with integrated protection against damage





Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

Flexible suction pad mounting. By flexing in all directions, this mounting allows the suction pad to better adapt itself to sloping workpieces.

Ürün

Tanım	Dişli 1 iç	Dişli 2 dış	H (mm)	Malzeme	L1 (mm)	L2 (mm)	Açı W (°)	Dikey yük (N/m2)	Bükme momenti (N/m2)	SW (mm)
K- 07 45 01 47	G 1/4	M 10 x 1.25	27,0	Steel, rubber	10,5	8,0	12	500	8,0	17
K- 07 45 01 48	G 1/4	G 1/4	27,0	Steel, rubber	12,0	12,0	12	750	10,0	17

Titiz kontrole rağmen hatalar önlenemez ve sorumluluk altında bırakmayan bilgiler hakkında hiçbir sorumluluk kabul edilmez.