

K-DRS MDR 5 M ENTLASTU VENT

»MDR 5« pressure switches, with unloading valve / on/off switch / flange 1/4, without motor protection circuit

HANSA FLEX

Özellikler

| | |
|-----------------------|------------------------------------|
| Akışkan sıcaklığı | -5 °C to +80 °C |
| maks. kapatma basıncı | 16 bar |
| Devre kapasitesi | 5,5 kW |
| Kontakt türü | NC (3-pole) |
| maks. çalışma sıklığı | 120 (electrical), 600 (mechanical) |
| Koruma sınıfı | IP 54 |



Açıklama

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
Diğer bilgiler, istek üzerinedir.

Açıklama

Three-phase version

Siparişe ilgili bilgiler

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Ek bilgiler

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

Ürün

| Tanım | Basıncılı hava bağlantısı | Ayarlama alanı |
|----------------|---------------------------|----------------|
| K- 07 30 24 25 | G 1/2 | 2,0 - 11,0 bar |
| K- 07 30 24 27 | G 1/2 | 2,5 - 16,0 bar |