

K-DRS MDR 5 M ENTLASTU VENT

»MDR 5« pressure switches, with unloading valve / on/off switch / flange 1/4, without motor protection circuit

HANSA FLEX

Özellikler

Akışkan sıcaklığı	-5 °C to +80 °C
maks. kapatma basıncı	16 bar
Devre kapasitesi	5,5 kW
Kontakt türü	NC (3-pole)
maks. çalışma sıklığı	120 (electrical), 600 (mechanical)
Koruma sınıfı	IP 54



Açıklama

G thread acc. to DIN EN ISO 228-1, with ISO flange plate (acc. to ISO 5211)
Diğer bilgiler, istek üzerinedir.

Açıklama

Three-phase version

Siparişe ilgili bilgiler

For use on devices that have to be vented whenever they are turned off, either because of safety regulations or for technical reasons. The pneumatic devices are disconnected from the system and simultaneously vented each time they are shut off.

Ek bilgiler

Important: A thermal, 3-pole overcurrent relay must be ordered together with these switches. Without this relay, the on/off mechanism does not work.

Ürün

Tanım	Basıncılı hava bağlantısı	Ayarlama alanı
K- 07 30 24 25	G 1/2	2,0 - 11,0 bar
K- 07 30 24 27	G 1/2	2,5 - 16,0 bar