



K-T-STUECKE IG IG AG 2

Tees, female-female-male

HANSA FLEX

Özellikler

| | |
|-----------------|------------------------------|
| Çalışma basıncı | 60 bar |
| İşletim ısısı | Max. 150 °C |
| Dişli iç | Parallel to DIN EN ISO 228-1 |
| Malzeme | Nikel kaplı pirinç |
| Dişli dış | conical acc. DIN 2999 |



Açıklama

Diğer bilgiler, istek üzerinedir.

Ürün

| Tanım | Mil | L1 (mm) | L2 (mm) | SW |
|----------------|---------|------------|------------|-------|
| K- 07 40 48 94 | M 5 | 22,5 | 11,0 | 9 mm |
| K- 07 40 11 16 | G/R 1/8 | 39,5 | 21,0 | 10 mm |
| K- 07 40 11 17 | G/R 1/4 | 49,0 | 23,5 | 13 mm |
| K- 07 40 11 18 | G/R 3/8 | 54,0 | 28,0 | 17 mm |
| K- 07 40 11 19 | G/R 1/2 | 64,5 | 33,5 | 21 mm |
| K- 07 40 11 20 | G/R 3/4 | 69,5 | 36,5 | 25 mm |
| K- 07 40 11 21 | G/R 1 | 84,0 | 45,0 | 30 mm |