


K-PROP REGELVE SENTRONIC D

Proportional control valves, digital, 24 VDC

HANSA**FLEX**

Özellikler

Akışkan sıcaklığı	0 - 60 °C
Ortam sıcaklığı	0 - 50 °C
Akışkanlar	Air or neutral gases ($\leq 50 \mu\text{m}$ filter specified)
Basınç aralığı	0 - 10 bar
Çalıştırma	0 to 10 V (on request: 0 to 20 mA or 4 to 20 mA)
İstenen değer elektrikli	0 - 10 V
Analog çıkış	0 - 10 V
Çalıştırılması	Proportional solenoid valve
Dijital çıkış	Pressure switch output PNP +/- 5%
Arıza güvenlik ayarı	Pressure relieved in case of loss of voltage
İç parçalar	POM
Yalıtım malzemesi	NBR
Gövde	Aluminium



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

Ever increasing requirements with regard to quality, precision, productivity, convenience, user friendliness and service represent tough challenges for industrial plant and production facilities. These challenges can only be mastered if physical quantities such as temperature, pressure, force, speed, torque, etc. are optimally adapted to the operating conditions of each installation. Stepless adjustment of these parameters is vital.

Proportional valves allow the medium to be varied as a function of an electronic input variable. By linking these valves to the electronics, it is possible to improve their accuracy and broaden their range of applications. A pressure regulator, for instance, needs to be suitable for several pressure ranges without having to adjust the pressure manually. Proportional valves control the output pressure in a closed control loop proportionally to the selected setpoint signal. This output pressure, in other words, is continually compared with the specified setpoint and automatically adjusted according to actual parameter values.

Ürün

Tanım	Bağlantı	DN	Akış (L/min)	B	C (mm)
K- 07 25 10 04	G 1/8	4	780	52,0 mm	112,0
K- 07 25 10 05	G 1/4	4	780	52,0 mm	112,0
K- 07 25 10 06	G 1/4	8	1750	66,0 mm	138,0
K- 07 25 10 07	G 3/8	8	1750	66,0 mm	138,0