


# K-VENTILSCHEIBE HDM 4

Valve discs for HDM valve terminal with 4 mm port

**HANSA FLEX**

## Özellikler

|                                |   |
|--------------------------------|---|
| <b>Akışkanlar</b>              | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| <b>Çalışma basıncı</b>         | Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)                      |
| <b>Kumanda basıncı</b>         | 3 - 7 bar   |
| <b>Sıcaklık sahası</b>         | -10 °C to +60 °C  |
| <b>Akış</b>                    | 200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8)  |
| <b>Kumanda sayısı</b>          | Max. 16 (e.g. 16 spring return valves)  |
| <b>Manüel yardımcı kumanda</b> | Latching (bistable), Monostable (non-latching) version also available on request                    |
| <b>Güç tüketimi</b>            | 0.6 W per pilot   |
| <b>Koruma sınıfı</b>           | IP 65   |



## Açıklama

Diğer bilgiler, istek üzerinedir.

## Açıklama

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

## Ek bilgiler

Important: The scope of supply does not include a connector. Please order separately.

## Ürün

| Tanım          | Fonksiyon  |
|----------------|--|
| K- 07 15 20 53 | 2 x 3/2-way, NC, monostable or 5/3-way, mid-position exhausted   |
| K- 07 15 20 58 | 2 x 3/2-way, NO, monostable or 5/3-way, mid-position pressurised |
| K- 07 15 20 55 | 3/2-way, NC, monostable and 3/2-way, NO, monostable              |
| K- 07 15 20 57 | 5/2-way, monostable  |
| K- 07 15 20 52 | 5/2-way, monostable (uses only one pin, two signals assigned)    |
| K- 07 15 20 54 | 5/2-way, bistable (pulse valve)                                  |
| K- 07 15 20 56 | 5/3-way, mid-position closed                                     |