
## K-HS RD

## Unidirectional banjo valves, pneumatic release, port 2 with female thread



| Özellikler         |  |
|--------------------|--|
| Çalışma basıncı    | 0.3 - 10 bar   |
| Kumanda basıncı    | 0.5 - 2.5 bar, depending on operating pressure                       |
| Akışkan sıcaklığı  | max. 60 °C   |
| Yerleştirme konumu | Any. The ring piece must be positioned before the valve is tightened |
| Malzeme            | Nikel kaplı pirinç   |
| Yalıtım malzemesi  | Perbunan   |





## **Açıklama**

Diğer bilgiler, istek üzerinedir.

## **Açıklama**

For stopping and positioning the cylinder movement: If a control signal is present at port 3 (see drawing), air can flow to and from the cylinder. If no control signal is present, the cylinder exhaust air is shut off by the unidirectional valve. <br/> <br/>br>The cylinder is stopped. Releasable unidirectional valves are screwed directly onto the cylinder instead of the normal pipe connections.

| Ürün           |        |        |            |           |           |  |
|----------------|--------|--------|------------|-----------|-----------|--|
| Tanım          | Port 1 | Port 2 | Bağlantı 3 | B<br>(mm) | C<br>(mm) |  |
| K- 07 15 07 04 | G 1/8  | G 1/8  | M 5        | 38,0      | 21,5      |  |
| K- 07 15 07 03 | G 1/4  | G 1/4  | G 1/8      | 43,0      | 25,4      |  |
| K- 07 15 07 05 | G 3/8  | G 3/8  | G 1/8      | 46,0      | 31,6      |  |
| K- 07 15 07 02 | G 1/2  | G 1/2  | G 1/8      | 52,0      | 32,0      |  |