K-WV 3/2 MANU K DREHHEBEL

3/2-way pilot valves, manually operated, with short wing lever, NC

Özellikler

Çalışma basıncı	2.5 - 10 bar (monostable)\n1.0 - 10 bar (bistable)\ nMax. vacuum 10 bar (external pilot air)
Sıcaklık sahası	-10 °C to +60 °C
Akış 6bar ve 10bar	550 Nl/min
Akış 6bar ve 5bar	400 Nl/min
Valf cismi	Alüminyum
Yay	Special steel
Piston	Aluminium
Yalıtım malzemesi	NBR



Açıklama

3 valve positions only in conjunction with a second 3/2-way valve.
Corresponds to a 5/3-way valve.
Diğer bilgiler, istek üzerinedir.

Ek bilgiler

Important: The scope of supply does not include a connector. Please order separately.

Ürün

Tanım	Bağlantı	Simge	Çalıştırılması	Şalter ayarları
K- 07 15 00 78	G 1/8	5	monostable	2
K- 07 15 00 79	G 1/8	6	bistabil	2
K- 07 15 00 80	G 1/8	7	monostable	3*
K- 07 15 00 81	G 1/8	8	bistabil	3*

Titiz kontrole rağmen hatalar önlenemez ve sorumluluk altında bırakmayan bilgiler hakkında hiçbir sorumluluk kabul edilmez.