
## K-WTST SAFETY BKR SCHA AN DR MULTI

SAFETY service unit sets, comprising a ball valve with silencer, startup valve and pressure regulator with lock cylinder



Özellikler				
Giriş basıncı	2 - 16 bar			
Çıkış basıncı	0.5 - 10 bar			
Sıcaklık sahası	Max. 60 °C			
Akışkanlar	Basınçlı hava			
Yalıtım malzemesi	NBR			
Кар	Polycarbonate (with bayonet lock) and bowl guard			
Yay kapağı	POM			
Filtre ünitesi	Cellpor (PE) 5 µm			
Gövde	Die-cast zinc			
Membran	NBR			
Drain valve	Semi-automatic			
Akış değeri ölçümü	At P1 = 8 bar, P2 = 6 bar and pressure drop $\Delta p$ = 1 bar			
Diğer bilgiler	see data sheets of the individual components (on request)			
Anschl. Entlüft. Küresel vana	Silencer			





## **Açıklama**

These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

## Siparişle ilgili bilgiler

The price does not include a padlock. Please order separately. For accessories and spare parts, refer to individual components: ball valve, start-up valve, pressure regulator, filter regulator, 2-piece service unit.

	-	
	PI I	n
.,	ru	

Tanım	Mil	Ayar aralığı	Akış (L/min)	A (mm)	В	C (mm)
K- 07 25 15 11	G 1/4	2 - 10 bar	1000	128,0	137,8 mm	94,0
K- 07 25 15 12	G 1/2	2 - 10 bar	4000	189,0	200,8 mm	122,0
K- 07 25 15 13	G 1	2 - 10 bar	12000	241,7	282,8 mm	157,0

12.12.2025 HANSA-FLEX AG www.hansa-flex.com