K-SPIR SCHL KUPPL SET LKM NW 7,6

Spiral hose and coupling kits, with safety couplings DN 7.6



Özellikler	
Çalışma basıncı	10 bar
Akışkan sıcaklığı	-20 °C to +60 °C



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

Ürün					
Tanım	Hortum ölçüsü	Ø spiral _(mm)	Çalışma uzunluğu m)		
K- 07 10 07 65	10 mm x 6,5 mm	52	2,0		
K- 07 10 07 66	10 mm x 6,5 mm	52	4,0		
K- 07 10 07 67	10 mm x 6,5 mm	52	6,0		
K- 07 10 07 68	10 mm x 6,5 mm	52	8,0		
K- 07 10 07 69	12 mm x 8 mm	65	2,0		
K- 07 10 07 70	12 mm x 8 mm	65	4,0		
K- 07 10 07 71	12 mm x 8 mm	65	6,0		
K- 07 10 07 72	12 mm x 8 mm	65	8,0		