

# K-SPIR SCHL KUPPL SET LKM NW 7,6

Spiral hose and coupling kits, with safety couplings DN 7.6

**HANSA FLEX**

## Özellikler

Çalışma basıncı 10 bar

Akışkan sıcaklığı -20 °C to +60 °C



## Açıklama

Diğer bilgiler, istek üzerinedir.

## Açıklama

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

## Ürün

| Tanım          | Hortum ölçüsü  | Ø spiral (mm) | Çalışma uzunluğu (m) |
|----------------|----------------|---------------|----------------------|
| K- 07 10 07 65 | 10 mm x 6,5 mm | 52            | 2,0                  |
| K- 07 10 07 66 | 10 mm x 6,5 mm | 52            | 4,0                  |
| K- 07 10 07 67 | 10 mm x 6,5 mm | 52            | 6,0                  |
| K- 07 10 07 68 | 10 mm x 6,5 mm | 52            | 8,0                  |
| K- 07 10 07 69 | 12 mm x 8 mm   | 65            | 2,0                  |
| K- 07 10 07 70 | 12 mm x 8 mm   | 65            | 4,0                  |
| K- 07 10 07 71 | 12 mm x 8 mm   | 65            | 6,0                  |
| K- 07 10 07 72 | 12 mm x 8 mm   | 65            | 8,0                  |