

# K-KALIBRIER-TEST UND SERVICE

Calibration, testing and service unit

**HANSA FLEX**

## Özellikler

Model	Calibration, testing and service unit
Hassasiyet	0,25% FS
Ölçme maddesi sıcaklığı	-20 °C to +80 °C
Ortam sıcaklığı	-10 °C to +50 °C
Ölçme maddesi dokunan parçalar	CrNi-steel with NBR seal
Gövde	Die-cast zinc



## Açıklama

Diğer bilgiler, istek üzerinedir.

## Açıklama

Service case for quick and precise pressure gauge calibration. Suitable for service and maintenance providers of all kinds as well as instrumentation control workshops and quality assurance. Simple operation using four buttons. The high sampling rate (100 measurements / second) guarantees an accurate analysis at the measuring point. Comprised of a CPG500 digital gauge and a CPP40 pneumatic hand test pump with a connecting cable for pressure generation. Operating manual, calibration certificate 3.1, two AA batteries and a protective rubber cap for the housing are enclosed. Includes a plastic emergency case with foam padding.

## Ek bilgiler

Further measuring ranges on request

## Ürün

Tanım	Ölçme alanı	Bağlantı
K- 07 20 12 70	-0.95 / +40 bar	G 1/4