

Özellikler

Çalışma basıncı	Max. 10 bar (at +20 °C)
Sertlik	52 Shore D±3
Kalibrasyon	External
Ortam sıcaklığı	-35 °C to +80 °C
Malzeme	Poliüretan



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

This externally calibrated plastic hose made of high-quality polyester PUR is extremely flexible with optimal mechanical characteristics and very high pressure resistance across a wide temperature range. It is permanently flexible, boasts very good resilience and can be laid with a narrow bending radius. Its other advantages include good abrasion resistance, very good low-temperature flexibility and very high elongation at break. The hose is also suitable for vacuum applications. It is resistant to many different oils and lubricants (a special resistance test is recommended in specific cases owing to the additives that are blended in by the manufacturers), aliphatic hydrocarbons and gases such as oxygen, ozone, helium, etc.

Ürün

Tanım	Ø hortum iç (mm)	Ø hortum dış (mm)	Bükme yarıçapı akışla ilgili (mm)	Renk	Bobin uzunluğu (m)
K- 07 10 05 47	2,6	4,0	17	Natural	25
K- 07 10 05 49	3,1	5,0	15	Natural	100
K- 07 10 05 48	3,1	5,0	15	mavi	100
K- 07 10 05 51	9,0	12,0	67	Natural	100
K- 07 10 05 52	9,0	12,0	67	siyah	100
K- 07 10 05 54	9,8	14,0	72	Natural	50
K- 07 10 05 53	9,8	14,0	72	mavi	50
K- 07 10 05 55	9,8	14,0	72	siyah	50
K- 07 10 05 56	11,0	16,0	88	Natural	50
K- 07 10 05 57	11,0	16,0	88	siyah	50