

K-RD MUFFE 246 IG AG

Sockets 246, reducing, female/male

HANSA FLEX

Özellikler

Yüze	Hot dip galvanised
Sıcaklık sahası	-20 °C to +300 °C (at 20 bar)
Bağlantı vida dişi	acc. ISO 7-1
Malzeme	Black malleable iron B350-10, design symbol A
Ruhsat	DIN DVGW



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

Acc. to DIN EN 10242 (formerly DIN 2950). The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. The fittings are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications.

Ek bilgiler

Further types and dimensions on request.

Ürün

Tanım	Dişli 1	Dişli 2
K- 07 40 37 26	Rp 3/8	R 1/4
K- 07 40 37 20	Rp 1/2	R 1/4
K- 07 40 37 21	Rp 1/2	R 3/8
K- 07 40 37 25	Rp 3/4	R 1/2
K- 07 40 37 15	Rp 1	R 1/2
K- 07 40 37 16	Rp 1	R 3/4
K- 07 40 37 19	Rp 1 1/4	R 3/4
K- 07 40 37 18	Rp 1 1/4	R 1
K- 07 40 37 17	Rp 1 1/2	R 1
K- 07 40 37 36	Rp 1 1/2	R 1 1/4
K- 07 40 37 22	Rp 2	R 1
K- 07 40 37 24	Rp 2	R 1 1/4
K- 07 40 37 23	Rp 2	R 1 1/2
K- 07 40 51 76	Rp 2 1/2	R 2
K- 07 40 51 77	Rp 3	R 2
K- 07 40 51 78	Rp 3	R 2 1/2