


K-V 340 IG IG

Unions 340, taper seat, female/female

HANSA FLEX

Özellikler

| | |
|--------------------|---|
| Yüzeý | Hot dip galvanised |
| Sıcaklık sahası | -20 °C to +300 °C (at 20 bar) |
| Baęlantı vida diři | acc. ISO 7-1 |
| Malzeme | Black malleable iron B350-10, design symbol A |
| Ruhsat | DIN DVGW |



Açıklama

Dięer bilgiler, istek üzerinedir.

Açıklama

Acc. to DIN EN 10242 (formerly DIN 2950). The classic - and the most popular - screw fitting series for pipe construction. These fittings are characterized by their high mechanical strength and surface quality to DIN 2444. They are completely coated with a layer of pure zinc and are therefore suitable for drinking water. They are also protected against rust. The fittings are used in pipe construction, plumbing and gas installations as well as a wide range of industrial applications.

Ek bilgiler

Further types and dimensions on request.

Ürün

| Tanım | Mil |
|----------------|-------------|
| K- 07 40 38 19 | Rp/Rp 1/4 |
| K- 07 40 38 22 | Rp/Rp 3/8 |
| K- 07 40 38 18 | Rp/Rp 1/2 |
| K- 07 40 38 21 | Rp/Rp 3/4 |
| K- 07 40 38 15 | Rp/Rp 1 |
| K- 07 40 38 17 | Rp/Rp 1 1/4 |
| K- 07 40 38 16 | Rp/Rp 1 1/2 |
| K- 07 40 38 20 | Rp/Rp 2 |
| K- 07 40 52 37 | Rp/Rp 2 1/2 |
| K- 07 40 52 38 | Rp/Rp 3 |