

# K-SVKM NW 7,6 AG ST-MS VZ

Quick disconnect couplings DN 7.6, galvanised steel / brass, male

**HANSA FLEX**



## Özellikler

Çalışma basıncı	Max. 16 bar
Akış hava	2.100 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Akışkan sıcaklığı	-20 °C to +100 °C
Gövde	Steel
Yay	Stainless-steel
Sürgü kovani	Hardened and nickel-plated steel
Yalıtım malzemesi	NBR

## Açıklama

Diğer bilgiler, istek üzerinedir.

## Açıklama

High-quality, one-hand quick disconnect couplings made of brass / steel for high flow rates. Specially designed for all applications susceptible to severe mechanical wear. Strong, impact and vibration-resistant design for demanding environments. The "stream line" type has an integrated hose stem.

## Ürün

Tanım	Bağlantı	Uzunluk (mm)	SW (mm)
K- 07 35 07 77	R 1/4 male	63,0	20
K- 07 35 07 78	R 3/8 male	61,0	20
K- 07 35 07 79	R 1/2 male	56,0	22

## Ek elemanlar

K-NIPPEL KUPPL NW7 AG VZ PTFE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, male threaded, FPM (PTFE coated) seal
K-NIPPEL KUPPL NW7 IG VZ 1	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel, female
K-NIPPEL KUPPL STREAM LINE	Plugs for couplings DN 7.2 - DN 7.8, hardened and galvanised steel »stream line«
K-TUE 7,2 7,8 ST VZ 2	Stems for couplings DN 7.2 - DN 7.8, hardened and galvanised steel