

# K-ZWEIHAND S VENTILE O GEH

Two-hand safety valve without housing

**HANSA FLEX**

## Özellikler

Akışkanlar	Filtered, unlubricated compressed air
Çalışma basıncı	2.5 - 8 bar
Sıcaklık sahası	-10 °C to +60 °C
Bağlantı	Push-in fitting for pipe 4 mm
Çalıştırılması	Pneumatic
Akış miktarı hava 6bar	85 NI/min
maks. zaman kaydırması giriş sinyali	0,4 s



## Açıklama

Diğer bilgiler, istek üzerinedir.

## Açıklama

This pushbutton panel according to EN574 Type III A is comprised of a dual manual control valve with a housing and manifold. The valve only generates an output signal if two synchronised input signals are received within < 0.4 sec. If one input signal is interrupted, the output signal is interrupted as well. An emergency stop valve with a mushroom pushbutton is included. The housing can be screwed to the wall in any position. The valve manifold can optionally be supplied without the housing and with a DIN bar adapter. Applications: Two-hand safety valve for start-of-cycle control on a pneumatically operated machine.

## Ürün

Tanım	Tanımlama	Bağlantı
K- 07 15 26 09	Two-hand safety valve without housing	Push-in fitting for 4 mm pipe
K- 07 15 26 10	mounting element	-