

K-MANO STAND U

Pressure gauges, CrNi steel, standard type, connection radial on bottom

HANSA FLEX

Özellikler

| | |
|-------------------|---|
| Tip | 131.11 |
| Model | Bourdon-tube pressure gauge, CrNi steel type |
| Uygulama | For gaseous, liquid, corrosive and not crystallising media which do not have high viscosity, also in corrosive atmosphere Clean Dry Air applications, machine and plant construction |
| Kalite sınıfı | 2,5 |
| Akışkan sıcaklığı | max. +100 °C |
| Ortam sıcaklığı | -40 °C to +60 °C |
| Gövde | CrNi steel |
| Kontrol camı | Polycarbonate |



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

Standard model manufactured entirely from CrNi steel, economical and reliable.

Ürün

| Tanım | Ölçme alanı | Ø (mm) | Bağlantı |
|----------------|---------------|-----------|----------|
| K- 07 20 03 82 | 0 - 1.0 bar | 40,0 | G 1/4 |
| K- 07 20 03 83 | 0 - 1.6 bar | 40,0 | G 1/4 |
| K- 07 20 03 84 | 0 - 2.5 bar | 40,0 | G 1/4 |
| K- 07 20 03 85 | 0 - 4.0 bar | 40,0 | G 1/4 |
| K- 07 20 03 86 | 0 - 6.0 bar | 40,0 | G 1/4 |
| K- 07 20 03 87 | 0 - 10.0 bar | 40,0 | G 1/4 |
| K- 07 20 03 88 | 0 - 16.0 bar | 40,0 | G 1/4 |
| K- 07 20 03 89 | 0 - 25.0 bar | 40,0 | G 1/4 |
| K- 07 20 03 90 | 0 - 40.0 bar | 40,0 | G 1/4 |
| K- 07 20 03 91 | 0 - 60.0 bar | 40,0 | G 1/4 |
| K- 07 20 03 92 | 0 - 100.0 bar | 40,0 | G 1/4 |
| K- 07 20 04 83 | 0 - 1.0 bar | 50,0 | G 1/4 |
| K- 07 20 04 84 | 0 - 1.6 bar | 50,0 | G 1/4 |
| K- 07 20 04 85 | 0 - 2.5 bar | 50,0 | G 1/4 |
| K- 07 20 04 86 | 0 - 4.0 bar | 50,0 | G 1/4 |
| K- 07 20 04 87 | 0 - 6.0 bar | 50,0 | G 1/4 |
| K- 07 20 04 88 | 0 - 10.0 bar | 50,0 | G 1/4 |
| K- 07 20 04 89 | 0 - 16.0 bar | 50,0 | G 1/4 |
| K- 07 20 04 90 | 0 - 25.0 bar | 50,0 | G 1/4 |
| K- 07 20 04 91 | 0 - 40.0 bar | 50,0 | G 1/4 |
| K- 07 20 04 92 | 0 - 60.0 bar | 50,0 | G 1/4 |
| K- 07 20 04 93 | 0 - 100.0 bar | 50,0 | G 1/4 |