

# K-MANO STAND U

Pressure gauges, CrNi steel, standard type, connection radial on bottom

**HANSA FLEX**

## Özellikler

Tip	131.11
Model	Bourdon-tube pressure gauge, CrNi steel type
Uygulama	For gaseous, liquid, corrosive and not crystallising media which do not have high viscosity, also in corrosive atmosphere Clean Dry Air applications, machine and plant construction
Kalite sınıfı	2,5
Akışkan sıcaklığı	max. +100 °C
Ortam sıcaklığı	-40 °C to +60 °C
Gövde	CrNi steel
Kontrol camı	Polycarbonate



## Açıklama

Diğer bilgiler, istek üzerinedir.

## Açıklama

Standard model manufactured entirely from CrNi steel, economical and reliable.

## Ürün

Tanım	Ölçme alanı	Ø (mm)	Bağlantı
K- 07 20 03 82	0 - 1.0 bar	40,0	G 1/4
K- 07 20 03 83	0 - 1.6 bar	40,0	G 1/4
K- 07 20 03 84	0 - 2.5 bar	40,0	G 1/4
K- 07 20 03 85	0 - 4.0 bar	40,0	G 1/4
K- 07 20 03 86	0 - 6.0 bar	40,0	G 1/4
K- 07 20 03 87	0 - 10.0 bar	40,0	G 1/4
K- 07 20 03 88	0 - 16.0 bar	40,0	G 1/4
K- 07 20 03 89	0 - 25.0 bar	40,0	G 1/4
K- 07 20 03 90	0 - 40.0 bar	40,0	G 1/4
K- 07 20 03 91	0 - 60.0 bar	40,0	G 1/4
K- 07 20 03 92	0 - 100.0 bar	40,0	G 1/4
K- 07 20 04 83	0 - 1.0 bar	50,0	G 1/4
K- 07 20 04 84	0 - 1.6 bar	50,0	G 1/4
K- 07 20 04 85	0 - 2.5 bar	50,0	G 1/4
K- 07 20 04 86	0 - 4.0 bar	50,0	G 1/4
K- 07 20 04 87	0 - 6.0 bar	50,0	G 1/4
K- 07 20 04 88	0 - 10.0 bar	50,0	G 1/4
K- 07 20 04 89	0 - 16.0 bar	50,0	G 1/4
K- 07 20 04 90	0 - 25.0 bar	50,0	G 1/4
K- 07 20 04 91	0 - 40.0 bar	50,0	G 1/4
K- 07 20 04 92	0 - 60.0 bar	50,0	G 1/4
K- 07 20 04 93	0 - 100.0 bar	50,0	G 1/4