

K-SVKM NW 7,8 IG H

Quick disconnect couplings DN 7.8 - for extremely high flow rates, female

HANSA FLEX

Özellikler

Çalışma basıncı	0 - 35 bar
Akış hava	2.100 l/min (at $\Delta p = 0.5$ bar)
Akışkan sıcaklığı	-20 °C to +40 °C
Dişli parçası	Nickel-plated brass
Valf cismi	Steel, QPQ treated
Kilidi açma kovanı	Extremely robust, ergonomic plastic
Valf, yuva	Brass
Akışkanlar	Only for clean compressed air
Contalar	NBR
Yay, patlama halkası, bilyeler	stain less steel



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

One-hand quick disconnect couplings, one side sealing, that combine high flow rates (approx. twice as high as the popular DN 7.2 standard coupling) with minimal coupling forces. Suitable for all applications with an above-average air requirement!

Ürün

Tanım	Bağlantı	Uzunluk (mm)	SW (mm)
K- 07 35 08 50	G 1/4 female	59,0	19
K- 07 35 08 51	G 3/8 female	59,0	19
K- 07 35 08 52	G 1/2 female	62,0	24

Ek elemanlar

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 7,2 7,8 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass