

# K-SVKM NW 7,8 AG VA

Quick disconnect couplings DN 7.8, stainless steel 1.4305, male

**HANSA FLEX**



## Özellikler

|                                |   |
|--------------------------------|---|
| Çalışma basıncı                | 0 - 35 bar, maximum static working pressure (non-pulsating) |
| Akış hava                      | 1.800 l/min (at 6 bar and $\Delta p = 0.5$ bar)             |
| Akışkan sıcaklığı              | -15 °C to +200 °C   |
| Mahfaza, kovan, valf gövdesi   | Stainless steel 1.4305                                      |
| Yay, patlama halkası, bilyeler | Stainless steel   |
| Yalıtım malzemesi              | FKM   |

## Açıklama

Diğer bilgiler, istek üzerinedir.

## Açıklama

One-hand quick disconnect couplings, one side sealing, made of stainless steel 1.4305. Ideal for: Pneumatic tools, laboratory equipment, chemical applications, instrumentation and control, safety systems, industrial plant engineering, mechanical engineering.

## Ürün

| Tanım          | Bağlantı   | Uzunluk (mm) | SW (mm) |
|----------------|------------|--------------|---------|
| K- 07 35 07 90 | G 1/4 male | 59,5         | 19      |
| K- 07 35 07 91 | G 3/8 male | 57,5         | 19      |
| K- 07 35 07 92 | G 1/2 male | 60,5         | 24      |

## Ek elemanlar

|                            |   |
|----------------------------|---|
| K-NIPPEL KUPPL NW7 AG VA 1 | Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, male   |
| K-NIPPEL KUPPL NW7 IG VA 2 | Plugs for couplings DN 7.2 - DN 7.8, stainless steel 1.4305, female |
| K-TUE 7,2 7,8 VA 1         | Stems for couplings DN 7.2 - DN 7.8, stainless steel 1.4305         |