

K-LKM S NW7,8 IG

Safety couplings DN 7.8, female

HANSA FLEX

Özellikler

Çalışma basıncı	maks. 20 bar
Akış hava	1.400 l/min (at 6 bar and $\Delta p = 0.5$ bar)
Akışkan sıcaklığı	-20 °C to +100 °C
Bağlantı valf gövdesi	Nickel-plated brass
Yay, bilyeler	Stainless-steel
Sürgü kovani	Anodised aluminium
Kilidi açma kovani	Hardened and nickel-plated steel
Yalıtım malzemesi	NBR



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

Safety air relief couplings for gaseous media. Combination of a sliding valve and a quick disconnect coupling! Connection is pressureless. Only a low spring force has to be overcome. Pressure only builds up when the blue sleeve is pushed forward. It is impossible to disconnect the hose either intentionally or inadvertently in this position. When the sliding sleeve is moved back into its home position, the air is relieved from the hose and the coupling can be disconnected.

Ürün

Tanım	Bağlantı	Uzunluk (mm)	SW (mm)
K- 07 35 08 85	G 1/4 female	75,0	19
K- 07 35 08 86	G 3/8 female	75,0	19
K- 07 35 08 87	G 1/2 female	80,0	24

Ek elemanlar

K-NIPP KUPPL NW7 SCHL MS NI K	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose with swivel nut and kink protector spring
K-NIPPEL KUPPL NW7 AG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, male
K-NIPPEL KUPPL NW7 IG MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, female
K-NIPPEL KUPPL NW7 SCHL MS NI	Plugs for couplings DN 7.2 - DN 7.8, nickel-plated brass, for hose
K-TUE 5 MS NI	Stems for couplings DN 7.2 - DN 7.8, nickel-plated brass