
# K-DVST OHNE REGLER

## Pressure booster without regulator



Özellikler				
Giriş basıncı	2 - 10 bar			
Çıkış basıncı	Max. 20 bar (regulated: max. 16 bar)			
Sıcaklık sahası	-10 °C to +50 °C (40 mm bore), -10 °C to +60 °C (63 mm bore)			
Akışkanlar	Filtered, unlubricated or lubricated compressed air (if lubrication is used, it must be continuous)			
Yalıtım malzemesi	NBR			
Basınç regülatörü	With plastic body			
Gövde	Aluminium, anodised			
Boru	Anodised aluminium jacket			
Montaj	Any position, with 4 mounting holes			
P2:P1	2:1			





#### **Açıklama**

For information about calculating the filling times for different tank sizes, refer to the above-mentioned data sheet available on our website Diğer bilgiler, istek üzerinedir.

#### **Açıklama**

Pressure multipliers (boosters) allow a separate compressed air store with up to double pressure to be installed for selected devices in a compressed air system without an external energy source, i.e. it is possible to work with a maximum pressure of 20 bar in a standard 10 bar system (maximum ratio 2:1). This is achieved using a double piston, which is operated by a combination of integrated check valves in such a way that the booster works automatically until the target pressure is reached in a compressed air tank and is then automatically switched off. A tank is always required to build up the pressure and store the compressed air!

#### Ek bilgiler

Fixing bracket with nut

Tanım	Bağlantı	Ø piston	Н	L	
		(mm)	(mm)	(mm)	
K- 07 25 08 64	G 1/8	40,0	64,0	194,0	
K- 07 25 08 66	G 3/8	63,0	98,0	290,0	

### Aksesuar

K-ZUBEH ERSATZ LUFT BOOSTER Accessories / spare parts for Air-air-multiplicator (booster)