


K-ZFL VENTILINSEL HDM

Intermediate plates for HDM valve terminal

Özellikler

| | |
|--------------------------------|---|
| Akışkanlar | Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. |
| Çalışma basıncı | Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard) |
| Kumanda basıncı | 3 - 7 bar |
| Sıcaklık sahası | -10 °C to +60 °C |
| Akış | 200 NI/min (Ø 4), 500 NI/min (Ø 6), 800 NI/min (Ø 8) |
| Kumanda sayısı | Max. 16 (e.g. 16 spring return valves) |
| Manüel yardımcı kumanda | Latching (bistable), Monostable (non-latching) version also available on request |
| Güç tüketimi | 0.6 W per pilot |
| Koruma sınıfı | IP 65 |



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Ek bilgiler

Important: The scope of supply does not include a connector. Please order separately.

Ürün

| Tanım | Fonksiyon |
|----------------|--|
| K- 07 15 22 51 | With additional pilots and exhausts |
| K- 07 15 22 52 | With separate pilots (for multi-pressure systems) |
| K- 07 15 22 44 | With separate exhausts (for multi-pressure system) |