
## K-WTEH SERIE ONE O DRS

Service units, »ONE« Series, without pressure switch



Özellikler			
Giriş basıncı	Max. 10 bar		
Sıcaklık sahası	-10 °C to +50 °C		
Akışkanlar	Basınçlı hava		
Koruma sınıfı	IP 65		
Çalışma basıncı	0.5 - 8 bar		
Basınç şalteri	Changeover contact		
Filtre ünitesindeki delik genişliği	20 μm		
Akış değeri ölçümü	At 6,3 bar and Δp = 1 bar		





## **Açıklama**

Diğer bilgiler, istek üzerinedir.

## **Açıklama**

Multifunctional service unit with 6 or 7 functions in a single device: 3/2-way valve (manually operated), filter with automatic drain valve, air ports, pressure regulator, pressure gauge, soft start valve and optional: pressure switch. This combination of extremely good flow rates and a wide range of functions integrated in a single, compact unit saves valuable space and is unmatched by any similar product available in the market! Soft starting independently of the load and easy replacement of the filter cartridge under pressure are just two of the other outstanding features of this amazing device.

## Siparişle ilgili bilgiler

This unit can also be supplied with many other combinations of functions and port sizes. We will be pleased to make you an offer to match your individual specification on request!

run

Orum						
Tanım	Bağlantı	Akış	Α	В	С	Gerilim
		(L/min)	(mm)		(mm)	
K- 07 25 13 79	G 1/4	2400	165,5	144,0 mm	35,0	24 V DC (for valves and pressure switch)
K- 07 25 13 80	G 3/8	3300	165,5	144,0 mm	35,0	24 V DC (for valves and pressure switch)
K- 07 25 13 81	G 1/2"	4000	165,5	144,0 mm	35,0	24 V DC (for valves and pressure switch)

13.12.2025 HANSA-FLEX AG www.hansa-flex.com