


# K-WV 3/2 5/2 NAMUR LB LF

3/2- and 5/2-way spool valves with NAMUR style interface and air spring

**HANSA FLEX**

## Özellikler

Akışkanlar	Air, neutral gases (filtered)
Çalışma basıncı	1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22)
İşletim ısısı	-20 °C to +50 °C
Bağlantı 1 - 3	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
Bağlantı 1/3 + 5	G 1/4 (Port 1), G 1/4 (Port 3 and 5)
Elektrik bağlantısı	Plug connector PG 9
Teslimat kapsamına dahildir	Plug connector PG 9, conversion plate, screws and seal
Güç tüketimi	3 W=5 VA~
Gövde	Anodised aluminium
Sürgüler	Stainless steel
Yalıtım malzemesi	NBR



## Açıklama

Diğer bilgiler, istek üzerinedir.

## Açıklama

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function.

Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

## Ürün

Tanım	Gerilim	Port 1	Bağlantı 3 + 5	DN	Akış (L/min)
K- 07 15 00 13	230 V, 50 Hz	G 1/4	G 1/4	7	1250
K- 07 15 00 14	24 V DC	G 1/4	G 1/4	7	1250