
# K-WTEH 3-TLG PC SCHU VARIOBLOC

Service units, 3-piece with polycarbonate bowl and bowl guard



Özellikler				
Giriş basıncı	Max. 16 bar (polycarbonate bowl), Max. 20 bar (metal bowl)			
Akışkan sıcaklığı	max. 50 °C			
Ortam sıcaklığı	Max. 50 °C (polycarbonate bowl), Max. 80 °C (metal bowl)			
Filtre ünitesindeki delik genişliği	40 μm			
Yalıtım malzemesi	NBR			
Yay kapağı	POM			
Gövde	Die-cast zinc			
Membran	NBR			
Damla örtüsü	PA			
Drain valve	Manual			
Akış değeri ölçümü	At P1 = 10 bar, P2 = 6 bar and pressure drop Δp = 1 bar			





### **Açıklama**

Diğer bilgiler, istek üzerinedir.

#### **Açıklama**

Two or three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: Simple handling, Convenient modular assembly thanks to innovative fasteners, Excellent flow values.

#### Siparişle ilgili bilgiler

Service units are also available with bowl guard or metal bowl. Service units are also available in other control ranges (0.5 - 6 bar and 0.5 - 16 bar) and in lockable version. Please ask for more information.

## Ek bilgiler

Service units are also available with bowl guard or metal bowl. Service units are also available in other control ranges.

#### Ürün

Tanım	Mil	Ayar aralığı	Akış	А	В	С
			(L/min)	(mm)		(mm)
K- 07 25 22 86	G 1/4	0.5 - 10 bar	1500	144,0	201,0 mm	68,0
K- 07 25 22 85	G 3/8	0.5 - 10 bar	1800	144,0	201,0 mm	68,0
K- 07 25 22 84	G 1/2	0.5 - 10 bar	3400	210,0	247,0 mm	98,0
K- 07 25 22 83	G 3/4	0.5 - 10 bar	5000	210,0	247,0 mm	98,0
K- 07 25 22 82	G 1	0.5 - 10 bar	5000	264,0	247,0 mm	98,0

23.11.2025 HANSA-FLEX AG www.hansa-flex.com