

# K-LKM S NW7,4 DREH IG VA

Safety couplings DN 7.4, stainless steel 1.4404, female, swivel type

**HANSA FLEX**

## Özellikler

Çalışma basıncı	maks. 10 bar
Akış hava	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Akışkan sıcaklığı	-20 °C to +150 °C
Gövde	Stainless steel 1.4404
Dişli	Stainless steel 1.4404
İç parçalar	Stainless steel 1.4404
Düğme, valf	Stainless steel 1.4404
Yalıtım malzemesi	FKM



## Açıklama

Not suitable for hitting / pulsating tools.  
Diğer bilgiler, istek üzerinedir.

## Açıklama

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

## Ek bilgiler

Not suitable for hitting / pulsating tools.

## Ürün

Tanım	Bağlantı	Uzunluk (mm)	SW (mm)
K- 07 35 12 79	G 1/4 female	71,5	21
K- 07 35 12 80	G 3/8 female	75,5	21
K- 07 35 12 81	G 1/2 female	77,5	24