## K-LKM S NW7,4 DREH IG VA

Safety couplings DN 7.4, stainless steel 1.4404, female, swivel type



Özellikler			
Çalışma basıncı	maks. 10 bar		
Akış hava	1.800 l/min (at 6 bar and Δp = 1 bar)		
Akışkan sıcaklığı	-20 °C to +150 °C		
Gövde	Stainless steel 1.4404		
Dişli	Stainless steel 1.4404		
İç parçalar	Stainless steel 1.4404		
Düğme, valf	Stainless steel 1.4404		
Yalıtım malzemesi	FKM		



## **Açıklama**

Not suitable for hitting / pulsating tools.

Diğer bilgiler, istek üzerinedir.

## **Açıklama**

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414. For the food processing, chemical and medical industries as well as pharmaceutical plant construction.

## Ek bilgiler

Not suitable for hitting / pulsating tools.

Ürün				
Tanım	Bağlantı	Uzunluk	SW	
		(mm)	(mm)	
K- 07 35 12 79	G 1/4 female	71,5	21	
K- 07 35 12 80	G 3/8 female	75,5	21	
K- 07 35 12 81	G 1/2 female	77,5	24	