K-DMUF FESTSTOFFHALTIGE MED

Pressure transmitter for viscous and solids-containing media, nonlinearity 0.2%

Özellikler

Tip	S-11
Voltaj	DC 10 (14) ... 30 V
Elektrik bağlantısı	With right-angle connector acc. to DIN EN 175301-803 A
Koruma sınıfı	IP 65 acc. to EN 60529
Çıkış sinyali	4 to 20 mA, 2-wire
Doğrusal olmama	0.2% of span
Akışkan sıcaklığı	-30 °C to +100 °C; (Range: 400 and 600 bar: -30 °C to +70 °C)
Ortam sıcaklığı	-20 °C to +80 °C
Ölçme maddesi dokunan parçalar	CrNi steel 1.4571
Gövde	CrNi steel 1.4571



Açıklama

Pressure transmitter in CrNi steel with flush diaphragm for measuring viscous, pasty, adhesive, crystallising, particle-laden or contaminated media, which would clog the pressure channel of conventional process connections. Applications: Electronic pressure measurement in the food and beverages sector, hydraulic power units or industrial applications in general.

Ek bilgiler

Further measuring ranges on request

There are also pressure converters with cooling fins available optionally on request for high media temperatures (up to +150 °C).

Ürün

Tanım	Ölçme alanı	Mil
K- 07 20 12 38	0 - 0.25 bar	G 1
K- 07 20 12 39	0 - 0.4 bar	G 1
K- 07 20 12 40	0 - 1.0 bar	G 1
K- 07 20 12 41	0 - 10.0 bar	G 1/2
K- 07 20 12 42	0 - 100.0 bar	G 1/2
K- 07 20 12 43	0 - 16.0 bar	G 1/2
K- 07 20 12 44	0 - 160.0 bar	G 1/2
K- 07 20 12 45	0 - 25.0 bar	G 1/2
K- 07 20 12 46	0 - 250.0 bar	G 1/2
K- 07 20 12 47	0 - 4.0 bar	G 1/2
K- 07 20 12 48	0 - 40.0 bar	G 1/2
K- 07 20 12 49	0 - 400.0 bar	G 1/2
K- 07 20 12 50	0 - 6.0 bar	G 1/2
K- 07 20 12 51	0 - 60.0 bar	G 1/2
K- 07 20 12 52	0 - 600.0 bar	G 1/2

Yedek Parçalar

K-ZUBEH DRUCKMESSUMFOR	Accessoires for pressure transmitters for viscous and solids-containing media, nonlinearity 0.2%

Titiz kontrole rağmen hatalar önlenemez ve sorumluluk altında bırakmayan bilgiler hakkında hiçbir sorumluluk kabul edilmez.