


K-L-STECKVER DREH AG-K BESCH 1

Male elbows, swivel type, conical male thread, coated

HANSA**FLEX**

Özellikler

Çalışma basıncı	Max. 16 bar
İşletim ısısı	-20 °C to +150 °C
Malzeme	Nikel kaplı pirinç
Bastırma halkası	Nickel-plated brass
Germe halkası	Stainless steel



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

Push-in fittings, manufactured entirely in nickel-plated brass. All parts with a parallel thread are supplied with an FPM O-ring. All parts with conical threads are coated with preCOTE 5 dispersion, all fittings in this series can thus also be used at high temperatures (medium compressed air).

Ürün

Tanım	Mil	Hortumun dış çapı için	L1 (mm)	L2 (mm)	SW
K-07 40 28 10	R 1/8	4 mm	20,0	20,0	13 mm
K-07 40 28 11	R 1/8	6 mm	21,0	20,0	13 mm
K-07 40 28 12	R 1/8	8 mm	24,0	20,0	13 mm
K-07 40 28 07	R 1/4	4 mm	20,0	25,0	14 mm
K-07 40 28 08	R 1/4	6 mm	21,0	25,0	14 mm
K-07 40 28 09	R 1/4	8 mm	24,0	25,0	14 mm
K-07 40 28 06	R 1/4	10 mm	27,0	26,0	16 mm
K-07 40 28 14	R 3/8	8 mm	24,0	28,0	18 mm
K-07 40 28 13	R 3/8	10 mm	27,0	30,0	18 mm
K-07 40 48 00	R 3/8	12 mm	29,0	32,5	20 mm
K-07 40 47 99	R 1/2	12 mm	29,0	35,5	22 mm