

K-WERKST-SCHLAUCH SOFT

Workshop hose soft

HANSA FLEX

Özellikler

İç Kat	Soft-PVC, black
Takviye Kat	Polyester örgüsü
Dış Kat	Soft-PVC, blue
Sıcaklık	-20 °C to +60 °C
Bobin uzunluğu	50 m



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Ürün

Tanım	Ø hortum iç (mm)	Ø hortum dış (mm)	Max. working pressure resistance at 23°C (bar)	Bükme yarıçapı min. (mm)
K- 07 10 10 33	6,3	11,0	15	23
K- 07 10 10 34	8,0	13,0	15	28
K- 07 10 10 35	9,0	14,5	15	32
K- 07 10 10 36	10,0	15,5	15	35
K- 07 10 10 37	12,7	19,0	15	45
K- 07 10 10 38	16,0	23,0	15	56
K- 07 10 10 39	19,0	26,5	15	67
K- 07 10 10 40	25,0	33,5	15	88