

K-WERKST-SCHLAUCH SOFT

Workshop hose soft

HANSA FLEX

Özellikler

| | |
|-----------------------|------------------|
| İç Kat | Soft-PVC, black |
| Takviye Kat | Polyester örgüsü |
| Dış Kat | Soft-PVC, blue |
| Sıcaklık | -20 °C to +60 °C |
| Bobin uzunluğu | 50 m |



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

Highly flexible hose for compressed air applications in workshop areas (compressed air feed for pneumatic tools, equipping assembly stations, etc.). Thanks to the even fabric reinforcement, this hose combines high pressure resistance, very good handling and high mechanical strength with excellent bond adhesion. The high level of ozone resistance further enhances the hose's durability and reliability. TÜV approved.

Ürün

| Tanım | Ø hortum iç (mm) | Ø hortum dış (mm) | Max. working pressure resistance at 23°C (bar) | Bükme yarıçapı min. (mm) |
|----------------|---------------------|----------------------|---|-----------------------------|
| K- 07 10 10 33 | 6,3 | 11,0 | 15 | 23 |
| K- 07 10 10 34 | 8,0 | 13,0 | 15 | 28 |
| K- 07 10 10 35 | 9,0 | 14,5 | 15 | 32 |
| K- 07 10 10 36 | 10,0 | 15,5 | 15 | 35 |
| K- 07 10 10 37 | 12,7 | 19,0 | 15 | 45 |
| K- 07 10 10 38 | 16,0 | 23,0 | 15 | 56 |
| K- 07 10 10 39 | 19,0 | 26,5 | 15 | 67 |
| K- 07 10 10 40 | 25,0 | 33,5 | 15 | 88 |