K-LECKAGESUCHGERAET
Leakage finder

Özellikler

Çalışma frekansı	40 kHz ± 2 kHz
Bağlantı	4-pin connection for headphones and charger, 3.5 mm stereo jack for connecting sensor and cable
Lazer	Wave length: 655 to 660 nm, Output power: 0.4 to 0.5 mW
Enerji beslemesi	Internal NiMH rechargeable battery
Sürekli işletim	Approx. 6 hours without laser / 4 hours with laser
Şarj süresi	Approx. 1.5 hours
Kullanım sıcaklığı	0 °C to +40 °C
Depolama sıcaklığı	-10 °C to +50 °C



Açıklama
Diğer bilgiler, istek üzerinedir.

Açıklama
Function: The annual energy cost of leaks in pneumatic and gas systems are high and avoidable. When these gases flow unused out of leaks, they create noises inaudible to the human ear. With the LS 100, even the smallest leaks can be heard from several metres distance. It transforms inaudible signals to a frequency that can be detected visually on the display and acoustically with the supplied sound-proof headphones. Use: leakage inspections of pneumatic, gas, steam and vacuum systems.
The advantages of the LS 100: Simple and quick measurement, even from distances of several metres Measurements can be taken on running systems, without affecting their operation
The device is quickly amortised by the high cost savings

Ürün

Tanım	Tanım
K- 07 25 19 53	Leak detection device, including accessories in a practical carrying case

Aksesuar

K-ALU-TELESKOPSTANGE	Aluminium-telescopic pole

Titiz kontrole rağmen hatalar önlenemez ve sorumluluk altında bırakmayan bilgiler hakkında hiçbir sorumluluk kabul edilmez.