K-SPIR SCHL KUPPL SET STAND MS

Spiral hose and coupling kit with standard coupling and push-in plug, bare brass



Özellikler	
Bağlantı tipi	connection nipples and coupling NW 7,2
İşletim ısısı	-40 °C to +74 °C



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Ürün					
Ø hortum iç (mm)	Ø hortum dış (mm)	Ø dış sargı (mm)	Max. working pressure resistance at 23°C (bar)	maks. çalışma uzunluğu (m)	
5,0	8,0	40	10	3,0	
5,0	8,0	40	10	6,0	
5,0	8,0	40	10	7,5	
6,3	9,5	60	10	3,0	
6,3	9,5	60	10	6,0	
6,3	9,5	60	10	7,5	
6,3	9,5	60	10	10,0	
8,0	12,0	80	9	3,0	
8,0	12,0	80	9	6,0	
8,0	12,0	80	9	7,5	
8,0	12,0	80	9	10,0	
	(mm) 5,0 5,0 5,0 6,3 6,3 6,3 6,3 8,0 8,0 8,0	(mm) (mm) 5,0 8,0 5,0 8,0 5,0 8,0 6,3 9,5 6,3 9,5 6,3 9,5 6,3 9,5 8,0 12,0 8,0 12,0 8,0 12,0 8,0 12,0	(mm) (mm) (mm) 5,0 8,0 40 5,0 8,0 40 5,0 8,0 40 6,3 9,5 60 6,3 9,5 60 6,3 9,5 60 6,3 9,5 60 8,0 12,0 80 8,0 12,0 80 8,0 12,0 80 8,0 12,0 80	(mm) (mm) (bar) 5,0 8,0 40 10 5,0 8,0 40 10 5,0 8,0 40 10 6,3 9,5 60 10 6,3 9,5 60 10 6,3 9,5 60 10 6,3 9,5 60 10 8,0 12,0 80 9 8,0 12,0 80 9 8,0 12,0 80 9 8,0 12,0 80 9	

Aksesuar	
K-DREHBARE VERSCHRAUBUNG	Swivel adapters

12.12.2025 HANSA-FLEX AG www.hansa-flex.com