

# K-SPIR SCHL KUPPL SET LKM NW 7,4

Spiral hose and coupling kit with pushbutton-type safety coupling (DN 7.4) and push-in plug, galvanised steel

**HANSA FLEX**

## Özellikler

|               |  |
|---------------|--|
| Bağlantı tipi | with pushbutton safety coupling NW 7,4 steel nipple galvanised |
| İşletim ısısı | -40 °C to +74 °C   |



## Açıklama

Diğer bilgiler, istek üzerinedir.

## Açıklama

Standard type or with braided reinforcements for high pressures. These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional nylon spiral hose, but with less tendency to loop and significantly better resistance to abrasion. There is consequently less danger of scratching coated or sensitive surfaces. The hose is extremely flexible and non-kinking.

Darbeli veya impulslu aletler için uygun değildir!

## Ürün

| Tanım          | Ø hortum iç (mm) | Ø hortum dış (mm) | Ø dış sargı (mm) | Max. working pressure resistance at 23°C (bar) | maks. çalışma uzunluğu (m) |
|----------------|------------------|-------------------|------------------|--|----------------------------|
| K- 07 10 12 71 | 5,0              | 8,0               | 40               | 10   | 3,0                        |
| K- 07 10 12 73 | 5,0              | 8,0               | 40               | 10   | 6,0                        |
| K- 07 10 12 75 | 5,0              | 8,0               | 40               | 10   | 7,5                        |
| K- 07 10 12 80 | 6,3              | 9,5               | 60               | 10   | 3,0                        |
| K- 07 10 12 82 | 6,3              | 9,5               | 60               | 10   | 6,0                        |
| K- 07 10 12 84 | 6,3              | 9,5               | 60               | 10   | 7,5                        |
| K- 07 10 12 78 | 6,3              | 9,5               | 60               | 10   | 10,0                       |
| K- 07 10 12 89 | 8,0              | 12,0              | 80               | 9  | 3,0                        |
| K- 07 10 12 91 | 8,0              | 12,0              | 80               | 9  | 6,0                        |
| K- 07 10 12 93 | 8,0              | 12,0              | 80               | 9  | 7,5                        |
| K- 07 10 12 87 | 8,0              | 12,0              | 80               | 9  | 10,0                       |

## Aksesuar

K-DREHBARE VERSCHRAUBUNG Swivel adapters