

K-WERKST-SCHLAUCH SOFT O

Workshop hose soft, oil resistant

HANSA FLEX

Özellikler

| | |
|-----------------------|--------------------------------|
| İç Kat | Soft-PVC, red, oil resistant |
| Takviye Kat | Polyester örgüsü |
| Dış Kat | Soft-PVC, black, oil resistant |
| Sıcaklık | -20 °C to +60 °C |
| Bobin uzunluğu | 50 m |



Açıklama

Diğer bilgiler, istek üzerinedir.

Açıklama

Workshop hose to meet the most demanding requirements. Extremely flexible (even at low temperatures), good resistance to oil and chemicals, long service life and excellent resistance to mechanical stresses (deformation under pressure, bending cycles, pressure pulses).

Ürün

| Tanım | Ø hortum iç (mm) | Ø hortum dış (mm) | Max. working pressure resistance at 23°C (bar) | Bükme yarıçapı min. (mm) |
|----------------|---------------------|----------------------|---|-----------------------------|
| K- 07 10 10 41 | 6,3 | 11,0 | 16 | 18 |
| K- 07 10 10 42 | 8,0 | 13,0 | 16 | 25 |
| K- 07 10 10 43 | 9,0 | 14,5 | 16 | 25 |
| K- 07 10 10 44 | 10,0 | 15,5 | 16 | 35 |
| K- 07 10 10 45 | 12,7 | 19,0 | 16 | 50 |
| K- 07 10 10 46 | 16,0 | 23,0 | 16 | 70 |
| K- 07 10 10 47 | 19,0 | 26,5 | 16 | 70 |
| K- 07 10 10 48 | 25,0 | 33,5 | 16 | 120 |