

# K-T AG-K ISO 7-1 2 SCH

Male branch tees, conical male thread acc. to ISO 7-1



**HANSA FLEX**

## Özellikler

Çalışma basıncı Max. 18 bar

Yalıtım malzemesi Buna-N

Malzeme Nikel kaplı pirinç



## Açıklama

Diğer bilgiler, istek üzerinedir.

## Ürün

Tanım	Mil	Hortum için	L1 (mm)	L2 (mm)	SW
K- 07 40 31 87	R 1/8	4 mm / 2 mm	49,0	16,0	9 mm
K- 07 40 31 88	R 1/8	5 mm / 3 mm	43,0	17,0	8 mm
K- 07 40 31 89	R 1/8	6 mm / 4 mm	44,0	17,0	9 mm
K- 07 40 31 90	R 1/8	8 mm / 6 mm	44,0	17,0	10 mm
K- 07 40 31 86	R 1/8	10 mm / 8 mm	51,0	18,5	11 mm
K- 07 40 31 84	R 1/4	6 mm / 4 mm	44,0	20,0	9 mm
K- 07 40 31 85	R 1/4	8 mm / 6 mm	44,0	20,0	12 mm
K- 07 40 31 83	R 1/4	10 mm / 8 mm	50,0	21,0	12 mm
K- 07 40 31 93	R 3/8	8 mm / 6 mm	46,0	22,0	12 mm
K- 07 40 31 91	R 3/8	10 mm / 8 mm	50,0	22,0	12 mm
K- 07 40 31 92	R 3/8	12 mm / 10 mm	62,0	24,0	17 mm
K- 07 40 31 81	R 1/2	10 mm / 8 mm	57,0	28,0	17 mm
K- 07 40 31 82	R 1/2	12 mm / 10 mm	62,0	26,0	17 mm