

HK GEH RK RB AG IG

Geril tepme valfi RK/RB için mahfaza

HANSA FLEX

Özellikler

Malzeme Galvanised steel

Çalışma basıncı maks. 700 bar .



Ürün

| Tanım | G | L (mm) | L1 (mm) | Ø D (mm) | Ø D1 (mm) | SW (mm) | Ağırlık (kg) |
|----------------------|--------|-----------|------------|-------------|--------------|------------|-----------------|
| HK GEH RKR B 0 AG IG | G 1/8" | 8,0 | 28,0 | 14,0 | 12,5 | 14 | 0,02 |
| HK GEH RKR B 1 AG IG | G 1/4" | 12,0 | 43,0 | 19,0 | 12,5 | 19 | 0,05 |
| HK GEH RKR B 2 AG IG | G 3/8" | 12,0 | 44,0 | 22,0 | 20,5 | 22 | 0,07 |
| HK GEH RKR B 3 AG IG | G 1/2" | 14,0 | 52,0 | 26,0 | 24,0 | 27 | 0,11 |
| HK GEH RKR B 4 AG IG | G 3/4" | 16,0 | 60,0 | 32,0 | 30,0 | 36 | 0,26 |

Aksesuar

HK RB Geril tepme valfi RB

HK RK Geril tepme valfi RK