

LKM HR ST DK

Geçmeli Kaplin, Dişi, Hava, Emniyetli

HANSA FLEX



Özellikler

Model	Hızlı Bağlantı-Dişi
Bağlantı 1	BSP dış diş silindirik
Bağlantı 2	
Çalışma basıncı	maks. 12 bar
Akış hava	1.800 l/min (at 6 bar and $\Delta p = 1$ bar)
Akışkan sıcaklığı	-20 °C to +70 °C
Gövde	Aluminium, anodised
Dişli	Nickel-plated brass
İç parçalar	Stainless steel
Düğme, valf	Hardened, galvanised steel
Yalıtım malzemesi	NBR

Açıklama

Not suitable for hitting / pulsating tools.
Diğer bilgiler, istek üzerinedir.

Açıklama

High-quality, robust and durable, one-hand quick disconnect safety couplings for high flow rates. When it is pressed for the first time, air is relieved from the coupling but the plug in the coupling remains locked. The plug is only disconnected when the pushbutton is pressed for the second time. The dreaded "whiplash effect" is avoided and the risk of injury to the operator virtually eliminated. The safety version conforms to ISO-Standard DIN EN ISO 4414.

Ürün

Tanım	Bağlantı dişlisi	Bağlantı	Uzunluk (mm)	SW (mm)
LKM 06 HR ST DK	G 1/4" -19	G 1/4 male	70,5	21
LKM 10 HR ST DK	G 3/8" -19	G 3/8 male	70,0	21
LKM 13 HR ST DK	G 1/2" -14	G 1/2 male	72,5	25