


SCHRAUBE M VZ

Alyan Civata

HANSA FLEX

Özellikler

| | |
|----------------|-----------------------|
| Model | Alyan vida |
| Standart | DIN 912 (ISO 4762) |
| Malzeme | Çelik 10.9 |
| Yüzey koruması | galvanised (tempered) |



Ürün

| Tanım | G | L1 (mm) | SW (mm) |
|----------------------|------|------------|------------|
| SCHRAUBE M 08-25 VZ | M 8 | 25 | 6 |
| SCHRAUBE M 08-30 VZ | M 8 | 30 | 6 |
| SCHRAUBE M 08-35 VZ | M 8 | 35 | 6 |
| SCHRAUBE M 08-40 VZ | M 8 | 40 | 6 |
| SCHRAUBE M 10-30 VZ | M 10 | 30 | 8 |
| SCHRAUBE M 10-35 VZ | M 10 | 35 | 8 |
| SCHRAUBE M 10-40 VZ | M 10 | 40 | 8 |
| SCHRAUBE M 10-45 VZ | M 10 | 45 | 8 |
| SCHRAUBE M 10-50 VZ | M 10 | 50 | 8 |
| SCHRAUBE M 12-35 VZ | M 12 | 35 | 10 |
| SCHRAUBE M 12-40 VZ | M 12 | 40 | 10 |
| SCHRAUBE M 12-45 VZ | M 12 | 45 | 10 |
| SCHRAUBE M 12-50 VZ | M 12 | 50 | 10 |
| SCHRAUBE M 12-55 VZ | M 12 | 55 | 10 |
| SCHRAUBE M 12-60 VZ | M 12 | 60 | 10 |
| SCHRAUBE M 14-45 VZ | | 45 | 12 |
| SCHRAUBE M 14-50 VZ | | 50 | 12 |
| SCHRAUBE M 14-55 VZ | | 55 | 12 |
| SCHRAUBE M 14-60 VZ | | 60 | 12 |
| SCHRAUBE M 14-65 VZ | | 65 | 12 |
| SCHRAUBE M 14-70 VZ | | 70 | 12 |
| SCHRAUBE M 14-75 VZ | | 75 | 12 |
| SCHRAUBE M 14-80 VZ | | 80 | 12 |
| SCHRAUBE M 16-50 VZ | M 16 | 50 | 14 |
| SCHRAUBE M 16-55 VZ | M 16 | 55 | 14 |
| SCHRAUBE M 16-60 VZ | M 16 | 60 | 14 |
| SCHRAUBE M 16-70 VZ | M 16 | 70 | 14 |
| SCHRAUBE M 16-80 VZ | M 16 | 80 | 14 |
| SCHRAUBE M 16-90 VZ | M 16 | 90 | 14 |
| SCHRAUBE M 16-100 VZ | M 16 | 100 | 14 |
| SCHRAUBE M 20-60 VZ | M 20 | 60 | 17 |
| SCHRAUBE M 20-65 VZ | M 20 | 65 | 17 |
| SCHRAUBE M 20-70 VZ | M 20 | 70 | 17 |
| SCHRAUBE M 20-90 VZ | M 20 | 90 | 17 |
| SCHRAUBE M 20-100 VZ | M 20 | 100 | 17 |
| SCHRAUBE M 20-110 VZ | M 20 | 110 | 17 |
| SCHRAUBE M 20-120 VZ | M 20 | 120 | 17 |

SW = Anahtar genişliği

Ürün türleri

SCHRAUBE M

aşağıdaki ürünlerin aksesuarıdır

| | |
|---------------|-----------------|
| FH (3000 PSI) | SAE Yarım Flanş |
| FH (6000 PSI) | SAE Yarım Flanş |
| VF (3000 PSI) | SAE Tam Flanş |
| VF (6000 PSI) | SAE Tam Flanş |