

No. 1907/2006 (REACH)
Printed 13.02.2017

revision 08.12.2016 (GB) Version 8.5

**Assambly Spray 400** 

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Name of product

Assambly Spray 400
Code-Nr. Hansa

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended intended purpose(s)

**Technical Aerosols** 

Corrosion Protection and Lubricant

1.3. Details of the supplier of the safety data sheet

Manufacturer/distributor HANSA-FLEX AG

Zum Panrepel 44, D-28307 Bremen Phone 0421/48907-0, Fax 0421/48907-48

E-Mail info@hansa-flex.com Internet www.hansa-flex.com

**Advice** Produktinformation

Phone +49(0)421/48907-0 Fax +49(0)421/48907-88

1.4. Emergency telephone number

Emergency advice Giftinformationszentrum Nord GIZ-Nord

Phone +49(0)551-19 240

### **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]

Hazard classes and Hazard Hazard Statements Classification procedure categories

 Aerosol 1
 H222, H229

 Skin Irrit. 2
 H315

 Eye Irrit. 2
 H319

 Aquatic Chronic 3
 H412

**Hazard Statements** 

H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H315 Causes skin irritation.H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP/GHS]





GHS02

GHS07



No. 1907/2006 (REACH) Printed 13.02.2017

revision 08.12.2016 (GB) Version 8.5

**Assambly Spray 400** 

## Signal word

Danger

#### **Hazard Statements**

H222 H229	Extremely flammable aerosol.  Pressurised container: May burst if heated.
H315 H319	Causes skin irritation. Causes serious eye irritation.
H412	Harmful to aquatic life with long lasting effects.

#### **Precautionary Statements**

P102	Keep out of reach of children.
P210 P211 P251 P264 P273 P280	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  Do not spray on an open flame or other ignition source.  Do not pierce or burn, even after use.  Wash hands thoroughly after handling.  Avoid release to the environment.  Wear protective gloves/protective clothing/eye protection/face protection.
P302 + P352 P305 + P351 + P338 P332 + P313 P337 + P313 P362	IF ON SKIN: Wash with plenty of soap and water. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing.
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
P501	Dispose of contents/container to hazardous or special waste collection point.

## 2.3. Other hazards

### Information pertaining to special dangers for human and environment

In extensive use, formation of flammable / explosive vapour-air mixture is possible.

### Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

not applicable

## 3.2. Mixtures

## Description

Lubrication spray based on solvents. Propellant: propane / butane.

## **Hazardous ingredients**

CAS No	EC No	Name	[% weight]	Classification according to Regulation (EC) No 1272/2008 [CLP/GHS]
67-63-0	200-661-7	propan-2-ol	< 2	Flam. Liq. 2, H225 / Eye Irrit. 2, H319 / STOT SE 3, H336
1305-62-0	215-137-3	calcium hydroxide	< 2	Skin Irrit. 2, H315 / Eye Dam. 1, H318
61641-74-5		propane/butane-mixture	40-50	Flam. Gas 1, H220 / Press Gas, H280
64742-49-0	265-151-9	Naphtha (petroleum) hydrotreated , free of aromatics (note P: < 0,1% benzene), Ethanol	15 - 19	Flam. Liq. 2, H225 / Asp. Tox. 1, H304 / Skin Irrit. 2, H315 / STOT SE 3, H336 / Aquatic Chronic 2, H411



No. 1907/2006 (REACH)
Printed 13.02.2017

revision 08.12.2016 (GB) Version 8.5

**Assambly Spray 400** 

**REACH** 

CAS No Name REACH registration number

67-63-0 propan-2-ol 01-2119457558-25

### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

#### **General information**

Remove moisted clothing immediately.

#### In case of inhalation

Remove the casualty into fresh air and keep him immobile.

In the event of symptoms refer for medical treatment.

#### In case of skin contact

In case of contact with skin wash off with soap and water.

Consult a doctor if skin irritation persists.

### In case of eye contact

In case of contact with eyes rinse thoroughly with plenty of water and seek medical advice.

#### In case of ingestion

Do not induce vomiting.

Medical treatment.

#### 4.2. Most important symptoms and effects, both acute and delayed

No information available.

## 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

## **SECTION 5: Firefighting measures**

## 5.1. Extinguishing media

## Suitable extinguishing media

Foam

Dry powder

Carbon dioxide

### Unsuitable extinguishing media

Full water jet

## 5.2. Special hazards arising from the substance or mixture

In case of fire formation of dangerous gases possible.

### 5.3. Advice for firefighters

### Special protective equipment for fire-fighters

Fire-fighting operations, rescue and clearing work under effect of combustion and smoulder gases just may be done with breathing apparatus.

#### **Additional information**

Cool endangered containers with water spray jet.



No. 1907/2006 (REACH)
Printed 13.02.2017

revision 08.12.2016 (GB) Version 8.5

**Assambly Spray 400** 

#### **SECTION 6: Accidental release measures**

## 6.1. Personal precautions, protective equipment and emergency procedures

#### For non-emergency personnel

Use personal protective clothing.

Keep away sources of ignition.

High risk of slipping due to leakage/spillage of product.

#### 6.2. Environmental precautions

Inform pollution control authorities if product gets into the sewerage systems or open waters.

Do not discharge into the drains or bodies of water..

Collect contaminated water / firefighting water separately.

Do not discharge into the drains/surface waters/groundwater.

### 6.3. Methods and material for containment and cleaning up

Take up with absorbent material (e.g. sand, kieselguhr, acid binder, general-purpose binder, sawdust).

After taking up the material dispose according to regulation.

#### **Additional Information**

Sort out leaky cans and dispose according to regulations.

#### 6.4. Reference to other sections

Safe handling: see section 7 Disposal: see section 13

Personal protection equipment: see section 8

### **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Care for thoroughly room ventilation, if necessary use in well ventilated area with local exhaust ventilation at workplace.

#### General protective measures

Do not inhale gases/vapours/aerosols.

### Hygiene measures

At work do not eat, drink and smoke.

Wash hands before breaks and after work.

#### Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking

Do not spray on a naked flame or any incandescent material.

Do not pierce or burn even after use.

Protect from heat and sunlight.

Vapours can form an explosive mixture with air.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Keep in closed original container.

Adhere to administrative regulations relating to storage of compressed gas cylinders / containers.

## Further information on storage conditions

Protect from heat and direct solar radiation.

Storage temperature may not exceed 50°C (=122°F).

Store container at cool and aired place.



No. 1907/2006 (REACH)
Printed 13.02.2017

revision 08.12.2016 (GB) Version 8.5

**Assambly Spray 400** 

## 7.3. Specific end use(s)

Recommendation(s) for intended use

See section 1.2

## **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Ingredients with occupational exposure limits to be monitored

CAS No	Name	Code	[mg/m3]	[ppm]	Remark
106-97-8	Butane	8 hours	1450	600	EH40/2005
		Short-term	1810	750	
1305-62-0	Calcium hydroxide	8 hours	5		EH40/2005
67-63-0	propan-2-ol	8 hours	999	400	EH40/2005
		Short-term	1250	500	

## **DNEL-/PNEC-values**

**DNEL** worker

CAS No	Substance name	Value	Code	Remark
67-63-0	propan-2-ol	888 mg/kg bw/day	DNEL long-term dermal (systemic)	
		500 mg/m3	DNEL long-term inhalative (systemic)	

#### **Additional advice**

The statutory local and national regulations have to be observed.

### 8.2. Exposure controls

## Respiratory protection

If ventilation insufficient, wear respiratory protection.

Breathing apparatus

## **Hand protection**

Glove material specification [make/type, thickness, permeation time/life, wetting resistance]:: Nitrile rubber; 0,4mm; 480min; 60min.

## Eye protection

tightly fitting goggles

### Other protection measures

protective clothing

## Appropriate engineering controls

Sufficient ventilation and exhaustion.

## **SECTION 9: Physical and chemical properties**

9.1. Information on basic physical and chemical properties

Appearance Colour Odour aerosol whitish solvent-like

**Odour threshold** 



No. 1907/2006 (REACH) Printed 13.02.2017

revision 08.12.2016 (GB) Version 8.5

**Assambly Spray 400** 

not determined

Important health, safety and environmental information					
	Value	Temperature	at	Method	Remark
pH value	not determined				
boiling point	not applicable				
Melting point / Freezing point	not determined				
Flash point	not applicable				Aerosol
Vapourisation rate	not determined				
Flammable (solid)	not determined				
Flammability (gas)	not determined				
Ignition temperature	> 250 °C				
Self ignition temperature	not determined				
Lower explosion limit	0,6 Vol-%				
Upper explosion limit	not determined				
Vapour pressure	3,5 bar	20 °C			
Relative density	1,4 g/ml	20 °C			calculated
Vapour density	not determined				
Solubility in water					insoluble
Solubility/other	not determined				
Partition coefficient n- octanol/water (log P O/W)	not determined				
Decomposition temperature	not determined				
Viscosity	not determined				

## **Oxidising properties**

No information available.

## **Explosive properties**

The product is considered non-explosive; nevertheless explosive vapour/air mixtures can be generated.

### 9.2. Other information

No information available.



No. 1907/2006 (REACH) Printed 13.02.2017

revision 08.12.2016 (GB) Version 8.5

**Assambly Spray 400** 

## **SECTION 10: Stability and reactivity**

#### 10.1. Reactivity

No information available.

#### 10.2. Chemical stability

No information available.

#### 10.3. Possibility of hazardous reactions

No information available.

#### 10.4. Conditions to avoid

Keep away from heat.

#### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

Carbon monoxide and carbon dioxide.

#### Thermal decomposition

Remark No decomposition if used as directed.

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

#### Acute toxicity/Irritation/Sensitization

Value/Validation Species Method Remark

Skin irritation irritant

Eye irritation irritant

## Experiences made from practice

Irritates mucous membranes.

Irritates eyes and skin.

Inhalation causes narcotic effect/intoxication.

#### **Additional information**

The product is to be handled with the caution usual with chemicals.

Other hazardous properties may not be excluded.

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

No information available.

## 12.2. Persistence and degradability

No information available.

## 12.3. Bioaccumulative potential

No information available.

#### 12.4. Mobility in soil



No. 1907/2006 (REACH)
Printed 13.02.2017

revision 08.12.2016 (GB) Version 8.5

**Assambly Spray 400** 

No information available.

#### 12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

#### 12.6. Other adverse effects

#### **General regulation**

Do not allow uncontrolled leakage of product into the environment.

Product is not allowed to be discharged into aquatic environment.

## **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Waste code No.

Name of waste

15 01 10\*

packaging containing residues of or contaminated by hazardous substances

Wastes marked with an asterisk are considered to be hazardous waste pursuant to Directive 2008/98/EC on hazardous waste.

#### Recommendations for the product

Remove in accordance with local official regulations.

#### Recommendations for packaging

Dispose of according to the local waste regulations.

#### **General information**

For proper waste disposal a complete emptying of the tin is necessary.

## **SECTION 14: Transport information**

	ADR/RID	IMDG	IATA-DGR
14.1. UN number	1950	1950	1950
14.2. UN proper shipping name	AEROSOLS	AEROSOLS	Aerosols, flammable
14.3. Transport hazard class(es)	2.1	2.1	2.1
14.4. Packing group	-	-	-
14.5. Environmental hazards	No	No	No

## 14.6. Special precautions for user

Caution: Gases

## 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

not applicable

## Land and inland navigation transport ADR/RID

Hazard label(s) 2.1

tunnel restriction code D

Classification code 5F

transport in "limited quantities" according to 3.4 ADR is possible



No. 1907/2006 (REACH) Printed 13.02.2017

revision 08.12.2016 (GB) Version 8.5

**Assambly Spray 400** 

## **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**VOC** standard

**VOC content** 64,3 % **VOC value** 461,8 g/L

#### 15.2. Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

### **SECTION 16: Other information**

#### Recommended uses and restrictions

National and local regulations concerning chemicals shall be observed.

For industrial use only.

#### **Further information**

Each user is responsible for the implementation of the national special regulations.

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Please observe the following disclaimer! --- Our safety data sheets have been compiled according to effective EU-directives, WITHOUT taking into account the special national directives concerning the handling of hazardous substances.

H220	Extremely flammable gas.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.