


属性	
接口 1	米制螺母螺纹
密封形式 1	带切割环的管接头
接口2+3	米制外螺纹,圆柱形
密封形式 2 + 3	24°内锥
结构类型	方向可调节的螺栓连接
结构形式	T形
标准	DIN 2353 ISO 8434-1
供货范围	带锁紧螺母和切割环的接套
原料	黄铜





## 提示

有关安装、装入、压力负荷和允许的工作温度的说明请您参阅管螺栓连接的技术信息。

		(mm)		L1 (mm)	L2 (mm)	L3 (mm)	SW (mm)	S1
L	PN 200	6	M 12 x 1.5	27	12,0	26,0	12	14
L	PN 200	8	M 14 x 1.5	29	14,0	27,0	12	17
L	PN 200	10	M 16 x 1.5	30	15,0	28,5	14	19
L	PN 200	12	M 18 x 1.5	32	17,0	29,0	17	22
L	PN 200	15	M 22 x 1.5	36	21,0	32,0	19	27
L	PN 200	18	M 26 x 1.5	40	23,5	36,0	24	32
S	PN 250	8	M 16 x 1.5	32	17,0	27,0	14	19
		L PN 200 L PN 200 L PN 200 L PN 200 L PN 200 S PN 250	L PN 200 8 L PN 200 10 L PN 200 12 L PN 200 15 L PN 200 15	L PN 200 8 M 14 x 1.5 L PN 200 10 M 16 x 1.5 L PN 200 12 M 18 x 1.5 L PN 200 15 M 22 x 1.5 L PN 200 18 M 26 x 1.5 S PN 250 8 M 16 x 1.5	L PN 200 8 M 14 x 1.5 29 L PN 200 10 M 16 x 1.5 30 L PN 200 12 M 18 x 1.5 32 L PN 200 15 M 22 x 1.5 36 L PN 200 18 M 26 x 1.5 40 S PN 250 8 M 16 x 1.5 32	L PN 200 8 M 14 x 1.5 29 14,0 L PN 200 10 M 16 x 1.5 30 15,0 L PN 200 12 M 18 x 1.5 32 17,0 L PN 200 15 M 22 x 1.5 36 21,0 L PN 200 18 M 26 x 1.5 40 23,5 S PN 250 8 M 16 x 1.5 32 17,0	L PN 200 8 M 14 x 1.5 29 14,0 27,0 L PN 200 10 M 16 x 1.5 30 15,0 28,5 L PN 200 12 M 18 x 1.5 32 17,0 29,0 L PN 200 15 M 22 x 1.5 36 21,0 32,0 L PN 200 18 M 26 x 1.5 40 23,5 36,0 S PN 250 8 M 16 x 1.5 32 17,0 27,0	L PN 200 8 M 14 x 1.5 29 14,0 27,0 12 L PN 200 10 M 16 x 1.5 30 15,0 28,5 14 L PN 200 12 M 18 x 1.5 32 17,0 29,0 17 L PN 200 15 M 22 x 1.5 36 21,0 32,0 19 L PN 200 18 M 26 x 1.5 40 23,5 36,0 24 S PN 250 8 M 16 x 1.5 32 17,0 27,0 14

结构系列:LL=非常轻 L=轻 S=重 - PN = 额定压力 PB = 最大工作压力 - Ø d2 = 管外直径

## 产品变体

, 442	•
VET	螺栓连接,T形, 钢
VET VA	螺栓连接,T形, 不锈钢